DIELECTRIC HV3 BOOTS

CLASS 3



Power Generation Power Distribution Construction Telecommunications Transport

An electrically insulating dielectric boot with an integral steel toe cap. The Respirex Dielectric HV3+boot allows high voltage live working at up to 26.5kV with every boot tested at 30kV.

Features

- Injection moulded using our proprietary HV3 compound for a seamless boot with superior electrical insulation properties
- Step voltage protection up to 35kV*
- Arc flash protection Meets the requirements of ASTM F2621-2019 at 40Cal/cm^{2**}
- 200 Joule epoxy coated steel toe cap
- · Lightweight for increased wearer comfort
- Superb low temperature flexibility down to -40°C
- Environmentally friendly PVC and Halogen free construction
- Biodegradeable & Phalate free
- Slip resistant moulded sole
- Cleated outsole for maximum grip
- Energy absorbing tunnel system in heel to EN 20345:2011 E
- Ergonomic cushioned insole (removable & machine washable) for greater wearer comfort
- Non-wicking knitted nylon lining
- Kick-off lug
- Adjustable height
- CE marked on the shaft with date and year of manufacture
- REACH Compliant

Care

- Machine washable at up to 40°C
- Five year shelf life

Options

- · Additional High Voltage DC test
- · Removable thermal liner

High Voltage Test

Each boot: 30kV AC - Leakage current <20mA over the three minute test cycle

Certification

- EN ISO 20345:2011 SB E SRC Safety Footwear
- EN 50321-1:2018 Class 3 AC Electrically Insulating Footwear
- PPE Regulation (EU) 2016/425
 Personal Protective Equipment
- Conforms to ASTM F1117

*Tested using the ASTM 2412-18a step voltage test method at 35kV with leakage current less than 1mA.

**The Respirex HV3 boot has been independently tested and meets the test requirements of ASTM F2621-2019.

②: www.respirexinternational.com **III**: +44 (0)1737 778600 **III**: info@respirex.co.uk Inquiries please contact: _
Respirex North America
Ph: (281) 350-5001
 Email: info@respirexna.com









Sizes

UK	3	4	5	6	7	8	9	10	11	12	13	14	15
EU	35	36	37	39	41	42	43	44	45	46	47	49	50
US	4	5	6	7	8	9	10	11	12	13	14	15	16

Specifications, configurations and colours are subject to change without notice.